


## 1550nm DFB LD Pigtail TOSA

**FT-D5653xxx-00**

**Features:**

- High stability DFB laser chip
- Data rate Up to 2.5Gbit/s
- Operate temperature from -40°C to +85°C
- LC&SC&FC Pigtail Connector



**Absolute Maximum Ratings**


Parameter	Symbol	Condition	Min	Max	Unit
Operating Case Temperature	$T_c$	--	-40	85	°C
Storage Temperature	$T_{stg}$	--	-40	85	°C
Lead solder Temperature	--	--		260	°C
Lead Soldering Time	--	--		10	s

**Optical/Electrical Characteristics (T=25°C, unless otherwise stated)**


Parameter	Symbol	Min	Typ	Max	Unit	Test Conditions
Optical Output Power	$P_o$	1.5	--	4.0	mW	CW, $I_{op}=30mA$
Threshold Current	$I_{th}$	--	10	15	mA	T=25 °C
Forward Voltage	$V_F$	--	1.1	1.6	V	
Operating Current	$I_{op}$	--	30	40	mA	CW, T=25 °C
Center Wavelength	$\lambda_c$	1530	1550	1570	nm	CW, T=25 °C
Side-mode Suppression Ratio	SMSR	30	40	--	dB	$I_{op}=30mA$
Spectral Width (-20 dB)	$\Delta\lambda$	--	--	1.0	nm	
Rise/Fall Times	$t_R, t_F$	--	--	0.1	ns	20% to 80%
Monitor Current	$I_{mon}$	100	--	1000	$\mu A$	$V_R=5 V$ ,
Monitor Dark Current	$I_D$	--	--	0.1	$\mu A$	$V_R=5 V$

**Dimensions And Pin Type**

**FC/PC Type**



**Pin Type**



**Order information**

FT-D5653xx-00

